



NexaParts B.V.
Duurzaamheidstraat 33
8094SC, Hattermeerbroek

E-MAIL info@nexaparts.nl
TEL +31 38 2024038
KVK 87151227

Spherical Bearing GEC440XT - 440 x 600 x 185 x 218mm

<https://www.nexaparts.com/spherical-bearing-gec440xt-440-x-600-x-185-x-218mm>

Specificaties

| | |
|-------------------------------|---------------------------------------|
| Productnummer | GEC440XT |
| Merk | NexaParts |
| Categorie | Radial Spherical Plain Bearings |
| afmeting | 440 x 600 x 185 x 218 mm |
| Materiaal | Hardchrom / PTFE weefsel |
| Kleur | Metaal |
| Style | GEC440XT (d (gat) 440 mm) |
| model | Gewrichtslager radiaal onderhoudsvrij |
| Gewicht | 196.00 Kg |
| Maintenance required | nee |
| B (Inner ring width) | 218 mm |
| Basic load ratings dynamic | 17310 kN |
| Basic load ratings statisch | 25970 kN |
| C (Width of outer ring) | 185 mm |
| CN Radial internal clearance | 0,145 - 0,285 mm |
| Color | Metaal |
| d (Bearing bore) | 440 mm |
| D (Outer diameter outer ring) | 600 mm |
| Material | Hardchrom / PTFE weefsel |
| Model | Gewrichtslager radiaal onderhoudsvrij |
| Model Description | 320-460mm |
| Norm | DIN ISO 12 240-1 C |
| Seals | No |
| Temperatuur range | -30°C up to +130°C |
| Tilting angle | 3 ° ? |
| Dimensions | 440 x 600 x 185 x 218 mm |

Pluspunten

- + Inner ring of bearing steel, hardened, sliding surface treated with chromium plating
- + Outer ring of bearing steel, axuak split twice (fixed with retaining ring), hardened and phosphated, with sliding surface of PTFE-fabric

Minpunten

- Please note: These bearings must not be lubricated. Lubrication reduces the lifetime!