



NexaParts B.V.
Duurzaamheidstraat 33
8094SC, Hattermeerbroek

E-MAIL info@nexaparts.nl
TEL +31 38 2024038
KVK 87151227

Spherical Bearing GE40ET-2RS/X - *GE40TGR-2RS - *GE40TXG3E-2RS - 40

<https://www.nexaparts.com/spherical-bearing-ge40et-2rsx-ge40tgr-2rs-ge40txg3e-2rs-40-x-62-x-22-x-28mm>

Specificaties

| | |
|-------------------------------|--|
| Productnummer | GE40ET-2RS/X - GE40TGR-2RS - GE40TXG3E-2RS |
| EAN | 7440846243200 |
| Merk | NexaParts |
| Categorie | Radial Spherical Plain Bearings |
| afmeting | 40 x 62 x 22 x 28 mm |
| Materiaal | RVS / PTFE weefsel versterkt |
| Kleur | Metaal |
| Style | GE40ET-2RS/X (d (gat) 40 mm) |
| model | Gewrichtslager radiaal onderhoudsvrij |
| Gewicht | 0.31 Kg |
| Maintenance required | nee |
| B (Inner ring width) | 28 mm |
| Basic load ratings dynamic | 175 kN |
| Basic load ratings statisch | 350 kN |
| C (Width of outer ring) | 22 mm |
| CN Radial internal clearance | 0 - 0,060 mm |
| Color | Metaal |
| d (Bearing bore) | 40 mm |
| D (Outer diameter outer ring) | 62 mm |
| Material | RVS / PTFE weefsel versterkt |
| Model | Gewrichtslager radiaal onderhoudsvrij |
| Model Description | 15-60mm |
| Norm | DIN ISO 12 240-1 E |
| Seals | Yes |
| Temperatur range | -30°C up to +130°C |
| Tilting angle | 7 ° ? |
| Dimensions | 40 x 62 x 22 x 28 mm |

Pluspunten

- + Alternative for Schaeffler INA GE40TGR-2RS
- + Alternative for SKF GE40TXG3E-2RS

Pluspunten

- + Inner ring of hardened stainless steel, Sliding surface treated with chromium plating
- + Outer ring of hardened stainless steel with firmly glued PTFE-fabric
- + Suffix-2RS: lip seals on both sides

Minpunten

- Please note: These bearings must not be lubricated. Lubrication reduces the lifetime!