



**NexaParts B.V.**  
Duurzaamheidstraat 33  
8094SC, Hattermeerbroek

E-MAIL [info@nexaparts.nl](mailto:info@nexaparts.nl)  
TEL +31 38 2024038  
KVK 87151227

## Rod End SI35ES-2RS - GIR35DO-2RS - SIA35ES-2RS - Bore 35MM x M36x3

<https://www.nexaparts.com/rod-end-si35es-2rs-gir35do-2rs-sia35es-2rs-bore-35mm-x-m36x3-bspf>

### Specificaties

Productnummer	SI35ES-2RS - GIR35DO-2RS - SIA35ES-2RS
EAN	7440846259270
Merk	NexaParts
Categorie	Rod Ends
Materiaal	C45 Verzinkt
Kleur	Metaal
Style	SI35ES-2RS - GIR35DO-2RS - SIA35ES-2RS
model	Stangkop onderhoudsplichtig
Gewicht	1.52 Kg
Model Description	15-80mm
Temperatuur range	-60°C up to +150°C
Color	Metaal
Material	C45 Verzinkt
Model	Stangkop onderhoudsplichtig
B (Inner ring width)	25 mm
Basic load ratings dynamic	79 kN
Basic load ratings statisch	146 kN
C1 max (Rod end width)	22 mm
CN Radial internal clearance	0,037 - 0,100 mm
d (Bearing bore)	35 mm
d2 max (Rod end diameter)	82 mm
h1 (Shank length)	125 mm
L3 min (Thread length)	60 mm
Maintenance Nippel	Ja
Maintenance required	Ja
Norm	DIN ISO 12 240-4-series E, Form F
Thread size	M36x3
Tilting angle	6 ° ?
Total height Rod end (L, L2, L4)	166

**Pluspunten**

- + Bearings of series GE..ES-2RS are firmly seated and located in the housing
- + DIN ISO 12 240-4-series E, Form F
- + Easy assembling
- + Grease nipple
- + Sliding Surface: steel/steel

**Minpunten**

- Rod ends with female thread requiring maintenance