



NexaParts B.V.
Duurzaamheidstraat 33
8094SC, Hattermeerbroek

E-MAIL info@nexaparts.nl
TEL +31 38 2024038
KVK 87151227

Rod End SA35ES - GAR35DO - Bore 35MM x M36x3 - BSP/F

<https://www.nexaparts.com/rod-end-sa35es-gar35do-bore-35mm-x-m36x3-bspf>

Specificaties

Productnummer	SA35ES - GAR35DO
Merk	NexaParts
Categorie	Rod Ends with Thread
Materiaal	C45 Verzinkt
Kleur	Metaal
Style	SA35ES - GAR35DO
model	Stangkop onderhoudsplichtig
Gewicht	1.41 Kg
Model Description	15-80mm
Temperatuur range	-60°C up to +150°C
Color	Metaal
Material	C45 Verzinkt
Model	Stangkop onderhoudsplichtig
B (Inner ring width)	25 mm
Basic load ratings dynamic	79 kN
Basic load ratings statisch	146 kN
C1 max (Rod end width)	22 mm
CN Radial internal clearance	0,037 - 0,100 mm
d (Bearing bore)	35 mm
d2 max (Rod end diameter)	82 mm
h (Shank length)	140 mm
L1 min (Thread length)	82 mm
Maintenance Nippel	Ja
Maintenance required	Ja
Norm	DIN ISO 12 240-4-series E, Form M
Thread size	M36x3
Tilting angle	6 ° ?
Total height Rod end (L, L2, L4)	181

Pluspunten

- + Bearings of series GE..ES are firmly seated and located in the housing
- + DIN ISO 12 240-4-series E, Form M

Pluspunten

- + Easy assembling
- + Grease nipple
- + Sliding Surface is Steel/steel

Minpunten

- Rod ends with male thread requiring maintenance