



**NexaParts B.V.**  
Duurzaamheidstraat 33  
8094SC, Hattermeerbroek

E-MAIL [info@nexaparts.nl](mailto:info@nexaparts.nl)  
TEL +31 38 2024038  
KVK 87151227

## Rod End SA60ES-2RS - GAR60DO-2RS - SAA60ES-2RS - Bore 60MM x

<https://www.nexaparts.com/rod-end-sa60es-2rs-gar60do-2rs-saa60es-2rs-bore-60mm-x-m52x3-bspf>

### Specificaties

Productnummer	SA60ES-2RS - GAR60DO-2RS - SAA60ES-2RS
EAN	7440846262218
Merk	NexaParts
Categorie	Rod Ends
Materiaal	C45 Verzinkt
Kleur	Metaal
Style	SA60ES-2RS - GAR60DO-2RS - SAA60ES-2RS
model	Stangkop onderhoudsplichtig
Gewicht	5.73 Kg
Model Description	15-80mm
Temperatuur range	-60°C up to +150°C
Color	Metaal
Material	C45 Verzinkt
Model	Stangkop onderhoudsplichtig
B (Inner ring width)	44 mm
Basic load ratings dynamic	245 kN
Basic load ratings statisch	450 kN
C1 max (Rod end width)	39 mm
CN Radial internal clearance	0,043 - 0,120 mm
d (Bearing bore)	60 mm
d2 max (Rod end diameter)	135 mm
h (Shank length)	210 mm
L1 min (Thread length)	115 mm
Maintenance Nippel	Ja
Maintenance required	Ja
Norm	DIN ISO 12 240-4-series E, Form M
Thread size	M52x3
Tilting angle	6 ° ?
Total height Rod end (L, L2, L4)	277,5

**Pluspunten**

- + Bearings of series GE..ES-2RS are firmly seated and located in the housing
- + DIN ISO 12 240-4-series E, Form M
- + Easy assembling
- + Grease nipple
- + Sliding Surface is Steel/steel

**Minpunten**

- Rod ends with male thread requiring maintenance